


PTFE Glass Cloth Tape

Name: PTFE Glass Cloth Tape

Construction

PTFE Glass Cloth

Silicone Adhesive



Specifications

Types	Backing Thickness	Total Thickness	Width	Roll Length	Roll ID
PGST0850	80um	130um	10~1000	10m	76mm (3")
PGST1350	130um	180um	10~1000	10m	76mm (3")

Applications

- ✧ Heat-sealing bags with variety of packaging machines
- ✧ Coating of guiding tracks, chutes, hoppers and metal molds which require mold-releasing
- ✧ Heat resistance insulation and protection
- ✧ For flame redundancy of electrical wires and cables

Typical Properties

Items	Units	Typical Values		Testing Methods
		PGST0850	PGST1350	
Adhesion to Steel	N/25mm	6.5~10.5	9.5~14.5	ASTM D3330
Temp Resistance	°C/30min	280	280	

Characteristics

- ✧ High mechanical and dielectric strength
- ✧ High temperature resistance
- ✧ High corrosive resistance
- ✧ Weather and water resistance

Storage Conditions & Shelf life

Store under normal conditions of 73°F (23°C) and 20~80% R.H. in the original carton. To obtain best performance, the product should be used within 12 months from the date of manufacture.

Notes

All above-mentioned techniques are the average values obtained after our several testing by acknowledged and reliable testing methods. In order to ensure the correct selection and using of our products, please make a through understanding both of the purposes and conditions on usage in advance, or notify us as to provide you with further explanation and service.